

# AFINOL

## ATF LG6

### Product description

Fully synthetic ultra-high performance long life ATF specifically designed for ZF 6-speeds automatic transmissions where the M.1375-4 specification is prescribed.

### Properties

- ✓ Excellent thermo- and oxidation stability.
- ✓ Excellent antiwear, antirust and anticorrosion technology
- ✓ High shear stability
- ✓ Very low pour point to ensure operation in very low temperature conditions
- ✓ High Viscosity index ensures adequate lubrication in both high operating & low starting temperatures.

### Performance Criteria

Exceeds the following performance criteria:

M1375.4  
Hyundai SP-IV  
VW G 055 005  
Toyota Type WS  
Nissan Matic S  
Mercon LV  
Dexron VI  
MB236.12

Technical specification	Method	Typical
Color:		Amber
Density @ 15°C:	ASTM D 4052	847 kg/m <sup>3</sup>
Kin. Viscosity at 40°C:	ASTM D 7042	35 mm <sup>2</sup> /s
Viscosity at 100°C:	ASTM D 7042	7,3 mm <sup>2</sup> /s
Viscosity Index:	ASTM D 2270	185
Flash Point COC:	ASTM D 92	>201°C
Pour Point:	ASTM D 97	-48°C

# AFINOL

MADE IN GERMANY